					0x-60x52			
				D60V52L	D60V52LM	D60V52T	D60V52TM	D60V52TI
Focal Plane						Second Focal Plane	_	
Low			10x					
Magnification	High			60x				
Effective Lens Diameter				52mm				
Body Tube Diameter						30mm		
	Low			-				
Exit Pupil	High			0.86mm (0.03inch)				
Field of View (real)		degree		2.0°				
	Low	ft/10		10.5 ft				
		m/10	-	3.49 m				
		degr		0.33°				
	High	ft/10		1.7 ft				
		m/1(0.58m				
	Low			88-99mm (3.5-3.9inch)				
Eye Relief High				95-101mm (3.7-4.0inch)				
1 Click Adjustment				1/8MOA 1/8MOA (1/4MOA*)				
Elevation Travel				60MOA				
Windage Travel				40MOA				
Focus				Side focus				
Focus Distance				10yd - infinity				
Reticle				CH 1/8dot 3/32dot 1/16dot Di-plex	MTR-1 MTR-2 MTR-3 MTR-4	CH 1/8dot 3/32dot 1/16dot Di-plex	MTR-1 MTR-2 MTR-3 MTR-4 MTR-FT	MTR-1, MTR-2 MTR-3, MTR-4 MTR-5 MTR-FT
Illuminated						-		0
Adjustment Dial Cap					 C	-		
Adjustment Dial					rmal	Tactical		
0-Set Device				- O				
In the Box				Flip Caps (Objctive and Eyepice) MD disk, Sunshade Lens Cloth				
Scope Size A				418mm (16.4inch) 420mm (16.5inch) 418mm (16.4inch) 420mm (16.5inch)				
			173mm (6.8inch)					
					60mm (2.4inch)			
			41mm (1.6inch)					
			E	142mm (5.6inch)				
		F	103mm (4.0inch) 105mm (4.1inch) 103mm (4.0inch) 105mm (4.1inch)					
G H			79mm (3.1inch)					
			57mm (2.2inch)					
Weight				700g (24.7oz)	710g (25.0oz)	720g (25.4oz)	730g (25.8oz)	760g (26.8oz)

Specification are subject to change without notice. ©Deon Optical Design Co.

